

Fans

## Axial Fan



## Complete range of axial fans

Whatever requirements and applications you may have, the axial fan range of Systemair is just as global and comprising. The fields of operation range from huge shopping centres, to underground carparks, up to tunnel- and MRT-projects in the whole world. Safety related fans such as smoke exhaust and explosion proof fans are part of our core competence.

Our quality management system which is certified to ISO 9001:2008 is one reason for our high quality standards. In our modern R&D centre we test in compliance with the international standards ISO and AMCA.

At Systemair you benefit from an international network from more than 50 companies. This guarantees you good response times even with international projects, as the contact person is never far away. You are sincerely invited to visit our production site for axial fans in Germany or our headquarters in Sweden to convince yourself on-site of our high quality standards.

This catalogue shows you the entire spectrum of our possibilities. Have a look at an axial fan program at its best and trust our decade-long experience. Our expert team will be pleased to be at your disposal!



## Disclose the secret of fresh air!

Since 1974 Systemair cares for the purity of an essential resource. Today Systemair is one of the leading ventilation companies worldwide. A success story, which started in Skinnskatteberg, Sweden, with the invention of the inline duct fan. This invention revolutionised the ventilation world.

Since then the company has continuously advanced and now offers a comprehensive range of products for all ventilation and air conditioning requirements. The experts of Systemair know the conditions and see the point whatever you need - the ventilation concept of a shopping centre,

domestic ventilation of a single family house or the ventilation of tunnels and metro stations. Over 6300 employees in more than 65 subsidiaries and 50 countries are available for the essential proximity to the customers.


This brochure presents the wide range of our medium pressure axial fans. For further information about our axial fan range and all the other Systemair products you can contact our experts in your local Systemair company or you can just visit our online catalogue on [www.systemair.com](http://www.systemair.com).



# Systemair around the globe

3  
Distribution Centers

50  
Countries with Sales Subsidiaries



27

Production Facilities

Always  
close to you!

# AXC(A) Axial fans

## Standard features:

- Aerofoil impeller with adjustable pitch angle
- Die cast aluminium hub and blades
- Lang casing, hot dip galvanized steel, to DIN EN ISO 1461
- Spun flanges for high rigidity, to DIN 24154 series 3
- Terminal box in IP65 mounted at the outside of the casing for easy wiring
- Single-or three-phase motors IP55, insulation class F, in accordance with EN 60034-5/IEC 85
- Suitable for operating temperatures of up to 55°C
- Inspection hole to verify correct direction of rotation

The Systemair AXC(A) range of long cased smoke extract axial fans is available in sizes from 315 up to 1.600 mm impeller diameter. The adjustable pitch angle setting offers a wide performance and maximum flexibility to match precisely individual airflow requirements. The AXC(A) axial fans have been performance tested in accordance with DIN ISO 5801 and AMCA 210 in a laboratory accredited by AMCA. High temperature testing at Technical University Munich, Germany.



Systemair Sdn Bhd certifies that AXC(A) Axial Fan shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.



The AMCA Certified Ratings Seal applies to air performance and sound for Model AXC(A) 315 to AXC(A) 1600 only.

The AMCA Certified Seal applies to FEG for models AXC(A) 1400 to AXC(A) 1600 only.

## High efficiency impellers

The die cast aerofoil aluminium impellers can be offered with full or fractional solidities, maximum efficiencies can be obtained.

## Sturdy casing

AXC(A) axial fan casings are heavy gauge, hot dip galvanized, with spun flanges for high rigidity. Long cased execution as standard stock range .

## Motors

Motor in the air stream. Frequency converter controllable only for standard ventilation on request. Single or two speed motors.

## Multi stage fans

For higher pressure drops two stage fans are offered. Two fans in series increase the available static pressure drop.



## Quality



Systemair is ISO 9001: 2008 approved. The Systemair quality is regularly monitored by TÜV Süd .



CERT NO: 2009-2-1779  
ISO ratings Program 001:2008

# Fan installations with accessories





### SOUND DATA



Single figure on performance curves are overall inlet L<sub>W</sub>I sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<40	-2	-6	-8	-9	-14	-19	-25	-31
	<80	-4	-3	-11	-12	-19	-22	-27	-32
25°	<40	-1	-7	-14	-12	-17	-20	-26	-30
	<80	-1	-7	-14	-14	-18	-22	-26	-30
40°	<40	-2	-6	-14	-5	-15	-21	-27	-33
	<80	-1	-7	-15	-7	-18	-23	-28	-32

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ , 1013hPa



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>W</sub>I sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
 Hub : 150mm




### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Inlet Levels									
Pitch Angle	$\Delta p_{stat}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<20	-3	-6	-6	-9	-14	-20	-32	-32
	<35	-2	-7	-9	-14	-19	-23	-38	-33
25°	<20	-2	-8	-10	-11	-15	-20	-25	-29
	<35	-1	-8	-11	-13	-17	-21	-25	-29
40°	<20	-2	-8	-7	-9	-16	-22	-28	-33
	<35	-2	-9	-8	-10	-18	-23	-27	-31



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<150	-2	-6	-8	-9	-11	-16	-22	-28
	<380	-2	-6	-8	-13	-15	-19	-22	-28
20°	<150	-2	-5	-12	-12	-13	-17	-20	-27
	<200	-2	-6	-10	-13	-14	-18	-22	-28
30°	<150	-2	-5	-13	-13	-12	-15	-19	-26
	<280	-2	-5	-9	-13	-14	-18	-21	-27
40°	<150	-2	-6	-13	-13	-9	-15	-20	-27
	<380	-2	-6	-12	-16	-11	-18	-23	-29



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
 Hub : 150mm




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	Δp stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<40	-3	-6	-7	-9	-14	-20	-26	-32
	<90	-2	-5	-10	-12	-16	-19	-25	-31
20°	<40	-2	-8	-9	-9	-14	-17	-23	-29
	<50	-3	-6	-9	-10	-14	-19	-25	-31
30°	<40	-2	-10	-10	-9	-12	-16	-23	-30
	<70	-2	-8	-10	-11	-15	-19	-25	-31
40°	<40	-3	-8	-10	-6	-12	-17	-24	-31
	<90	-2	-7	-12	-7	-14	-19	-25	-31

 AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013 \text{ hPa}$ 


- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
 Hub : 150mm



### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<20	-3	-5	-7	-11	-16	-21	-27	-33
	<40	-2	-6	-9	-12	-16	-20	-26	-32
20°	<20	-3	-7	-7	-10	-13	-18	-25	-31
	<24	-3	-6	-8	-11	-15	-21	-27	-33
30°	<20	-3	-7	-7	-8	-12	-18	-25	-32
	<30	-2	-7	-7	-10	-14	-19	-25	-31
40°	<20	-4	-8	-6	-7	-13	-19	-26	-32
	<90	-3	-8	-7	-8	-15	-21	-27	-33



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.


Pitch Angle	Δp stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<200	-3	-7	-8	-10	-10	-15	-20	-26
	<360	-3	-6	-5	-12	-12	-19	-24	-28
25°	<200	-2	-5	-15	-20	-20	-23	-25	-20
	<360	-1	-8	-16	-19	-20	-22	-23	-17
40°	<200	-5	-2	-8	-10	-11	-15	-21	-27
	<360	-3	-5	-9	-10	-12	-17	-22	-28



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end corrector.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{stat}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<50	-4	-8	-7	-6	-12	-17	-23	-29
	<90	-4	-3	-10	-8	-15	-21	-26	-30
25°	<50	-1	-9	-12	-11	-15	-17	-12	-6
	<90	-2	-10	-13	-13	-16	-17	-13	-8
40°	<50	-2	-6	-8	-9	-13	-19	-25	-31
	<90	-3	-7	-8	-10	-15	-20	-26	-32



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-1</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	ΔP stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<20	-6	-6	-5	-8	-13	-19	-25	-31
	<40	-2	-6	-6	-9	-16	-22	-26	-30
25°	<20	-4	-10	-12	-14	-17	-15	-9	-6
	<40	-4	-9	-11	-13	-14	-13	-6	-3
40°	<20	-3	-6	-7	-10	-15	-21	-27	-33
	<40	-4	-6	-7	-11	-16	-21	-27	-33



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
 Hub : 150mm




### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<200	-3	-8	-8	-7	-11	-15	-20	-26
	<450	-3	-8	-8	-8	-12	-17	-21	-28
20°	<200	-3	-6	-11	-8	-11	-15	-18	-24
	<290	-3	-4	-7	-8	-13	-17	-20	-26
30°	<200	-2	-6	-14	-11	-11	-15	-19	-25
	<400	-2	-5	-12	-12	-13	-17	-21	-27
40°	<200	-3	-7	-15	-6	-10	-15	-20	-26
	<450	-3	-4	-15	-6	-12	-16	-22	-28



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
 Hub : 150mm


### SOUND DATA



Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
$10^\circ$	<50	-6	-5	-5	-9	-13	-18	-24	-30
	<110	-4	-4	-7	-10	-15	-18	-24	-30
$20^\circ$	<50	-3	-9	-6	-9	-13	-16	-22	-28
	<70	-3	-6	-6	-10	-14	-17	-23	-29
$30^\circ$	<50	-3	-10	-8	-7	-12	-15	-21	-27
	<100	-2	-8	-9	-10	-14	-18	-24	-29
$40^\circ$	<50	-5	-12	-4	-7	-13	-18	-24	-30
	<110	-3	-13	-4	-9	-14	-20	-26	-32

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013 \text{ hPa}$



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{stat}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<25	-5	-5	-6	-10	-15	-20	-26	-32
	<50	-3	-5	-7	-11	-16	-21	-27	-33
20°	<25	-5	-5	-6	-10	-13	-18	-24	-30
	<30	-3	-5	-6	-10	-14	-19	-25	-31
30°	<25	-4	-5	-6	-8	-12	-17	-23	-29
	<45	-3	-6	-7	-9	-13	-18	-24	-29
40°	<25	-8	-5	-4	-8	-13	-19	-25	-31
	<50	-5	-4	-5	-10	-15	-20	-26	-32



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
 Hub : 150mm




### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	ΔP stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<250	-2	-8	-11	-10	-9	-13	-17	-23
	<450	-2	-8	-6	-9	-9	-14	-21	-27
25°	<250	-5	-4	-2	-13	-18	-16	-18	-15
	<450	-4	-4	-11	-21	-25	-25	-26	-23
40°	<250	-4	-8	-6	-11	-9	-17	-22	-26
	<500	-4	-8	-5	-11	-9	-17	-22	-26



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct and correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Inlet Levels									
Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<70	-5	-8	-6	-5	-9	-14	-20	-26
	<120	-5	-3	-6	-6	-12	-20	-26	-31
25°	<70	-4	-2	-12	-18	-16	-18	-14	-15
	<120	-1	-4	-14	-20	-17	-19	-15	-16
40°	<70	-6	-4	-9	-7	-15	-20	-24	-28
	<120	-5	-3	-9	-7	-15	-19	-23	-27



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



## SOUND DATA



Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<35	-6	-6	-5	-6	-11	-16	-22	-28
	<50	-3	-5	-6	-10	-16	-23	-28	-33
25°	<35	-2	-8	-15	-17	-16	-16	-15	-16
	<50	-1	-9	-16	-19	-18	-18	-16	-17
40°	<35	-4	-6	-7	-11	-17	-21	-25	-29
	<50	-3	-6	-7	-10	-16	-20	-24	-28

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ , 1013hPa



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end corrective.





### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<250	-3	-8	-9	-8	-10	-13	-18	-24
	<650	-3	-9	-8	-10	-13	-16	-21	-26
20°	<250	-3	-9	-13	-8	-7	-14	-16	-22
	<400	-4	-7	-9	-9	-9	-14	-18	-23
30°	<250	-3	-12	-13	-8	-6	-14	-18	-23
	<500	-2	-10	-13	-10	-7	-16	-20	-25
40°	<250	-3	-10	-14	-9	-6	-14	-19	-25
	<550	-3	-10	-13	-9	-9	-17	-21	-27



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-11</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA


Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<70	-5	-5	-5	-7	-10	-15	-21	-27
	<150	-5	-4	-7	-9	-13	-18	-22	-26
20°	<70	-6	-10	-6	-4	-11	-14	-19	-24
	<100	-4	-6	-6	-6	-11	-15	-20	-26
30°	<70	-9	-10	-6	-3	-12	-16	-21	-26
	<130	-5	-7	-6	-4	-12	-17	-21	-25
40°	<70	-7	-10	-6	-3	-12	-17	-23	-29
	<140	-6	-9	-5	-5	-13	-18	-23	-28



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ , 1013hPa





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<35	-5	-5	-5	-8	-12	-18	-24	-30
	<70	-3	-6	-7	-11	-15	-19	-23	-27
20°	<35	-7	-7	-4	-7	-12	-16	-21	-26
	<45	-5	-6	-5	-8	-12	-17	-23	-28
30°	<35	-8	-7	-4	-7	-13	-18	-23	-27
	<60	-5	-5	-4	-7	-14	-18	-22	-26
40°	<35	-8	-7	-4	-7	-13	-19	-25	-31
	<65	-7	-6	-4	-9	-15	-20	-25	-30



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat.}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<300	-6	-3	-7	-9	-11	-14	-20	-25
	<550	-7	-4	-7	-7	-11	-14	-20	-25
25°	<300	-8	-5	-4	-9	-18	-19	-22	-26
	<600	-8	-5	-4	-9	-19	-20	-23	-27
40°	<300	-7	-4	-6	-9	-19	-22	-26	-30
	<550	-7	-4	-4	-10	-19	-23	-26	-29



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<80	-2	-5	-9	-10	-14	-19	-24	-30
	<140	-3	-6	-6	-10	-14	-20	-25	-31
25°	<80	-4	-3	-8	-17	-18	-21	-25	-32
	<150	-4	-3	-8	-18	-19	-22	-26	-33
40°	<80	-3	-5	-8	-18	-21	-25	-29	-34
	<140	-3	-3	-9	-18	-22	-25	-28	-32



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA



Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<35	-2	-6	-8	-10	-15	-20	-25	-31
	<60	-3	-4	-8	-10	-16	-21	-27	-33
25°	<35	-2	-5	-12	-16	-19	-22	-28	-35
	<65	-2	-5	-13	-17	-20	-23	-29	-36
40°	<35	-2	-5	-12	-18	-21	-25	-30	-35
	<60	-2	-5	-12	-18	-22	-25	-29	-33

AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013\text{hPa}$



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<300	-6	-3	-10	-8	-12	-15	-18	-25
	<800	-7	-4	-8	-6	-15	-18	-22	-28
20°	<300	-6	-3	-11	-8	15	-16	-18	-24
	<450	-7	-4	-10	-7	-16	-16	-20	-25
30°	<300	-7	-4	-11	-3	-14	-15	-19	-25
	<700	-8	-5	-12	-3	-17	-17	-21	-26
40°	<300	-7	-4	-14	-3	-16	-16	-20	-25
	<700	-8	-5	-10	-3	-16	-18	-22	-27



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.


		Inlet Levels							
Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<80	-2	-8	-7	-11	-14	-17	-24	-31
	<200	-3	-7	-5	-14	-17	-21	-25	-32
20°	<80	-2	-9	-6	-14	-15	-17	-23	-29
	<120	-2	-9	-6	-14	-15	-18	-23	-29
30°	<80	-3	-10	-3	-13	-14	-18	-24	-31
	<170	-5	-11	-2	-16	-17	-21	-26	-32
40°	<80	-4	-13	-3	-15	-16	-20	-25	-31
	<170	-5	-10	-3	-15	-18	-22	-27	-32



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels						
Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Octave Band Centre Frequency (Hz)						
		63	125	250	500	1K	2K	4K
10°	<35	-3	-5	-8	-10	-13	-18	-25
	<90	-3	-4	-9	-13	-17	-21	-26
20°	<35	-4	-5	-8	-12	-13	-18	-24
	<55	-4	-5	-8	-12	-14	-19	-24
30°	<35	-5	-3	-7	-11	-14	-19	-26
	<80	-6	-3	-8	-14	-16	-21	-27
40°	<35	-6	-3	-6	-12	-15	-19	-25
	<80	-5	-3	-6	-13	-16	-21	-26



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
Hub : 150mm




### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	Δp stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<400	-6	-3	-5	-11	-11	-15	-20	-25
	<620	-7	-4	-6	-8	-9	-14	-21	-27
25°	<400	-10	-7	-2	-10	-17	-20	-23	-26
	<520	-10	-7	-2	-10	-17	-19	-23	-26
40°	<400	-10	-7	-3	-7	-16	-19	-23	-27
	<550	-10	-7	-2	-8	-17	-20	-23	-27



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<100	-2	-4	-10	-10	-14	-19	-24	-31
	<160	-3	-5	-7	-8	-13	-20	-26	-33
25°	<100	-6	-2	-9	-16	-19	-22	-26	-32
	<130	-6	-2	-10	-16	-18	-22	-25	-31
40°	<100	-7	-2	-7	-16	-19	-23	-27	-33
	<140	-7	-2	-8	-16	-20	-23	-27	-33



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<45	-2	-6	-10	-10	-16	-21	-27	-34
	<70	-3	-5	-8	-9	-15	-22	-28	-35
25°	<45	-2	-5	-12	-16	-20	-23	-28	-34
	<60	-2	-5	-12	-16	-19	-22	-27	-33
40°	<45	-3	-4	-11	-16	-20	-24	-29	-35
	<60	-3	-4	-11	-17	-21	-24	-29	-35



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


Axial Fan  
Hub : 150mm


### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



		Inlet Levels							
Pitch Angle	$\Delta P_{stat}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<500	-7	-4	-8	-7	-10	-13	-15	-20
	<930	-7	-4	-7	-6	-12	-16	-20	-25
20°	<500	-7	-4	-10	-7	-14	-16	-17	-22
	<700	-7	-4	-4	-7	-15	-17	-19	-24
30°	<500	-7	-4	-10	-5	-13	-16	-19	-23
	<700	-7	-4	-9	-5	-15	-17	-21	-25
40°	<500	-9	-6	-9	-3	-15	-17	-22	-28
	<730	-9	-6	-10	-3	-15	-17	-22	-27



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.


Pitch Angle	$\Delta P_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<120	-3	-7	-6	-9	-12	-14	-19	-27
	<230	-3	-6	-5	-11	-15	-19	-24	-30
20°	<120	-3	-9	-6	-13	-15	-16	-21	-27
	<200	-3	-3	-6	-14	-16	-18	-22	-28
30°	<120	-4	-9	-4	-12	-15	-18	-22	-28
	<180	-4	-8	-4	-14	-17	-20	-24	-29
40°	<120	-5	-9	-3	-14	-16	-21	-27	-33
	<180	-6	-9	-2	-14	-17	-22	-27	-32



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta p_{stat}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<50	-5	-5	-7	-9	-12	-16	-22	-30
	<100	-3	-4	-8	-13	-15	-20	-26	-32
20°	<50	-4	-5	-8	-12	-13	-16	-22	-28
	<90	-2	-5	-8	-13	-15	-19	-24	-30
30°	<50	-5	-4	-7	-12	-15	-18	-24	-29
	<80	-4	-4	-7	-13	-16	-20	-24	-29
40°	<50	-5	-3	-7	-13	-17	-22	-28	-34
	<80	-6	-3	-7	-13	-17	-22	-27	-32



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301.
- Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA



Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	ΔP stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<400	-8	-5	-3	-10	-11	-14	-18	-21
	<720	-11	-8	-2	-8	-10	-13	-19	-24
25°	<400	-10	-7	-2	-12	-15	-20	-24	-29
	<720	-10	-7	-2	-14	-15	-19	-23	-27
40°	<400	-11	-8	-2	-10	-13	-18	-23	-29
	<600	-11	-8	-1	-13	-15	-19	-24	-29

AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ , 20°C, 1013hPa



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	ΔP stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<100	-5	-2	-10	-10	-13	-17	-21	-29
	<180	-7	-2	-7	-9	-12	-18	-25	-31
25°	<100	-7	-1	-12	-15	-20	-24	-29	-34
	<180	-7	-1	-13	-15	-19	-23	-27	-32
40°	<100	-8	-1	-10	-13	-18	-23	-29	-33
	<180	-8	-1	-12	-14	-19	-24	-29	-33



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{stat}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<40	-3	-6	-9	-11	-14	-19	-26	-34
	<80	-3	-4	-8	-10	-15	-20	-27	-35
25°	<40	-2	-6	-12	-16	-20	-25	-30	-35
	<80	-2	-7	-12	-15	-19	-23	-28	-32
40°	<40	-2	-5	-10	-14	-19	-25	-30	-34
	<70	-2	-6	-12	-15	-20	-25	-29	-33



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
Hub : 150mm



### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<600	-9	-6	-10	-6	-7	-9	-13	-19
	<1100	-8	-5	-7	-4	-10	-13	-18	-24
20°	<600	-9	-6	-11	-4	-10	-12	-16	-19
	<800	-9	-6	-12	-4	-10	-13	-16	-20
30°	<600	-9	-6	-11	-3	-11	-13	-18	-22
	<950	-9	-6	-9	-3	-10	-14	-18	-21
40°	<600	-7	-4	-10	-5	-12	-14	-20	-25
	<1000	-8	-5	-10	-5	-11	-14	-19	-24



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-1}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA


Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<150	-5	-10	-6	6	-8	-12	-18	-26
	<270	-5	-5	-3	-9	-12	-16	-23	-31
20°	<150	-5	-11	-3	-10	-12	-16	-19	-25
	<200	-5	-11	-3	-10	-13	-16	-20	-25
30°	<150	-5	-10	-3	-10	-12	-17	-21	-27
	<230	-6	-9	-3	-10	-14	-18	-21	-27
40°	<150	-3	-9	-4	-10	-13	-19	-24	-30
	<260	-4	-9	-4	-10	-13	-18	-23	-27

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013 \text{ hPa}$



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<70	-7	-6	-5	-6	-9	-15	-21	-29
	<120	-4	-3	-6	-10	-14	-20	-26	-33
20°	<70	-7	-4	-6	-9	-12	-16	-21	-26
	<100	-7	-4	-5	-9	-13	-16	-21	-27
30°	<70	-6	-4	-6	-10	-13	-18	-23	-29
	<110	-6	-4	-6	-11	-15	-18	-23	-29
40°	<70	-5	-4	-6	-11	-15	-20	-25	-30
	<120	-5	-4	-6	-10	-14	-19	-24	-28



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<400	-9	-6	-6	-12	-10	-11	-13	-19
	<700	-9	-6	-3	-8	-7	-10	-14	-21
25°	<400	-10	-7	-2	-13	-14	-18	-21	-26
	<800	-11	-8	-2	-14	-10	-15	-20	-24
40°	<400	-10	-7	-2	-12	-14	-18	-22	-27
	<680	-9	-6	-2	-13	-14	-18	-22	-26

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013 \text{ hPa}$ 


- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p$ stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<120	-5	-3	-11	-7	-9	-12	-18	-26
	<200	-5	-2	-8	-6	-9	-14	-20	-28
25°	<120	-7	-1	-13	-14	-18	-21	-26	-31
	<200	-7	-1	-13	-9	-13	-18	-23	-29
40°	<120	-7	-2	-12	-14	-18	-22	-26	-31
	<170	-5	-2	-13	-14	-18	-21	-26	-31



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<50	-3	-7	-9	-9	-10	-15	-21	-29
10°	<80	-3	-4	-7	-7	-11	-16	-23	-31
25°	<50	-2	-6	-12	-14	-18	-22	-27	-32
25°	<90	-1	-7	-9	-10	-15	-20	-25	-31
40°	<50	-2	-6	-11	-14	-18	-23	-28	-33
40°	<75	-2	-6	-12	-14	-18	-23	-27	-32



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA



Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<30	-2	-9	-6	-7	-10	-16	-24	-32
	<50	-1	-7	-5	-7	-11	-17	-27	-35
25°	<30	-1	-11	-13	-16	-20	-24	-30	-35
	<55	1	-12	-9	-12	-17	-22	-28	-34
40°	<30	-1	-10	-13	-16	-21	-24	-29	-35
	<45	-1	-11	-13	-16	-20	-24	-29	-34

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013 \text{ hPa}$



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<500	-8	-5	-11	-9	-9	-8	-10	-15
	<1240	-9	-6	-9	-5	-4	-9	-14	-21
20°	<500	-7	-4	-10	-7	-10	-13	-15	-19
	<1000	-8	-5	-11	-7	-6	-8	-12	-18
30°	<500	-8	-5	-10	-7	-10	-13	-17	-22
	<1170	-6	-3	-10	-7	-11	-14	-18	-22
40°	<500	-7	-4	-9	-7	-10	-13	-17	-23
	<1000	-7	-4	-9	-7	-10	-13	-18	-23



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
 Hub : 150mm




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<150	-4	-10	-8	-8	-7	-9	-14	-22
	<310	-5	-8	-4	-4	0	-14	-21	-29
20°	<150	-3	-9	-6	-9	-12	-14	-17	-24
	<250	-4	-10	-7	-6	-8	-12	-18	-24
30°	<150	-3	-9	-6	-9	-12	-16	-21	-26
	<300	-2	-9	-6	-10	-13	-17	-21	-26
40°	<150	-3	-8	-6	-9	-12	-16	-22	-27
	<260	-3	-8	-7	-9	-12	-17	-22	-25



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
  - The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<60	-7	-8	-7	-6	-7	-10	-18	-26
10°	<140	-6	-4	-5	-5	-11	-17	-24	-31
20°	<80	-5	-6	-6	-9	-11	-14	-19	-26
20°	<120	-9	-8	-5	-6	-9	-14	-21	-29
30°	<80	-5	-5	-6	-9	-13	-17	-22	-27
30°	<130	-5	-6	-7	-9	-13	-17	-21	-26
40°	<60	-4	-6	-6	-9	-13	-18	-24	-29
40°	<120	-5	-6	-7	-9	-13	-18	-22	-25



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


Axial Fan  
Hub : 150mm



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<40	-8	-7	-7	-5	-7	-12	-20	-28
	<80	-7	-3	-3	-7	-13	-19	-27	-33
20°	<40	-7	-4	-6	-9	-11	-14	-22	-28
	<70	-7	-5	-5	-7	-11	-14	-21	-28
30°	<50	-6	-4	-7	-10	-14	-18	-23	-28
	<80	-6	-6	-6	-9	-13	-17	-22	-27
40°	<40	-6	-4	-7	-9	-14	-20	-25	-30
	<70	-6	-4	-7	-9	-14	-19	-22	-25



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA


Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<400	-8	-5	-9	-11	-8	-8	-10	-13
	<800	-10	-7	-11	-11	-5	-7	-11	-16
25°	<400	-7	-4	-7	-10	-11	-14	-18	-23
	<950	-7	-4	-6	-8	-6	-10	-15	-22
40°	<400	-7	-4	-6	-9	-11	-13	-16	-21
	<600	-7	-4	-6	-11	-12	-14	-17	-22

AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ , 20°C, 1013hPa



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA



Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<100	-4	-8	-10	-7	-7	-9	-12	-21
	<200	-6	-11	-10	-4	-6	-10	-15	-24
25°	<100	-3	-5	-9	-10	-13	-17	-22	-26
	<240	-3	-5	-7	-5	-9	-14	-21	-26
40°	<100	-4	-5	-9	-10	-13	-15	-21	-26
	<160	-3	-5	-11	-11	-14	-16	-21	-26

AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ , 20°C, 1013hPa



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



Inlet Levels										
Pitch Angle	$\Delta p_{stat}$ [Pa]	Octave Band Centre Frequency (Hz)								
		63	125	250	500	1K	2K	4K	8K	
10°	<50	-6	-8	-7	-5	-7	-10	-16	-25	
	<90	-8	-10	-7	-5	-8	-12	-20	-29	
25°	<50	-3	-6	-8	-10	-14	-18	-23	-27	
	<110	-3	-6	-5	-7	-11	-18	-22	-26	
40°	<50	-3	-6	-8	-10	-13	-17	-22	-27	
	<70	-3	-7	-9	-11	-13	-17	-22	-27	



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{12}$  watts, calculated per AMCA International Standard 301.

- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA



Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<30	-7	-9	-6	-6	-7	-11	-19	-28
	<50	-10	-10	-6	-5	-9	-14	-23	-32
25°	<30	-3	-6	-7	-10	-14	-19	-24	-28
	<65	-3	-6	-4	-8	-13	-19	-23	-27
40°	<30	-3	-6	-7	-10	-13	-18	-23	-28
	<40	-3	-7	-8	-11	-13	-18	-23	-28

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013 \text{ hPa}$



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





## SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{stat}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<800	-11	-8	-13	-8	-7	-6	-7	-12
	<1350	-8	-5	-10	-7	-3	-7	-10	-16
20°	<800	-7	-4	-13	-6	-10	-12	-15	-18
	<1250	-6	-3	-16	-6	-7	-10	-14	-20
30°	<800	-8	-5	-12	-4	-10	-13	-15	-19
	<1350	-8	-5	-14	-4	-11	-12	-15	-19
40°	<800	-7	-4	-13	-7	-11	-13	-16	-22
	<1250	-7	-4	-14	-6	-11	-13	-16	-21



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<200	-7	-12	-8	-7	-6	-7	-12	-20
	<350	-4	-9	-6	-3	-7	-10	-16	-25
20°	<200	-3	-12	-5	-9	-11	-14	-17	-22
	<320	-2	-16	-5	-6	-9	-13	-19	-25
30°	<200	-4	-11	-4	-9	-12	-15	-19	-25
	<350	-5	-13	-4	-10	-12	-14	-19	-23
40°	<200	-3	-12	-5	-10	-12	-15	-20	-25
	<300	-3	-13	-5	-10	-12	-15	-20	-25



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	Δp stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<90	-10	-9	-6	-6	-5	-9	-16	-24
	<150	-6	-6	-4	-5	-7	-12	-20	-29
20°	<90	-6	-6	-5	-8	-11	-14	-18	-23
	<140	-6	-6	-4	-6	-10	-15	-19	-24
30°	<90	-6	-5	-5	-9	-12	-15	-20	-25
	<150	-7	-5	-6	-9	-11	-15	-19	-23
40°	<90	-6	-6	-6	-8	-11	-16	-21	-26
	<140	-6	-6	-6	-8	-11	-16	-21	-26



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<50	-11	-7	-6	-5	-6	-11	-19	-27
	<90	-7	-4	-3	-6	-9	-15	-24	-32
20°	<50	-10	-2	-7	-9	-12	-15	-20	-25
	<80	-12	-2	-5	-8	-12	-16	-21	-26
30°	<50	-9	-2	-7	-10	-13	-17	-23	-28
	<90	-11	-2	-8	-10	-12	-17	-21	-25
40°	<50	-8	-3	-7	-9	-12	-17	-23	-28
	<80	-10	-3	-7	-8	-12	-17	-22	-27



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.


Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<700	-8	-5	-7	-10	-6	-7	-8	-14
	<1200	-11	-8	-4	-6	-5	-6	-10	-17
25°	<700	-8	-5	-7	-8	-10	-11	-16	-22
	<1200	-9	-6	-8	-9	-6	-9	-14	-20
40°	<700	-7	-4	-7	-8	-11	-13	-17	-23
	<1000	-6	-3	-7	-9	-11	-13	-17	-23



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA



Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<180	-5	-7	-10	-7	-7	-7	-14	-23
	<320	-8	-4	-6	-5	-6	-9	-15	-24
25°	<180	-4	-6	-7	-9	-11	-15	-21	-26
	<320	-5	-7	-8	-5	-8	-13	-19	-25
40°	<180	-4	-6	-7	-10	-12	-16	-22	-25
	<250	-2	-6	-8	-10	-12	-16	-22	-25

AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ , 20°C, 1013hPa



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{stat}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<80	-5	-6	-8	-6	-7	-10	-17	-25
	<140	-6	-3	-6	-5	-8	-12	-20	-28
25°	<80	-4	-5	-8	-9	-13	-18	-23	-29
	<140	-5	-6	-6	-6	-10	-16	-22	-28
40°	<80	-4	-5	-8	-10	-14	-19	-23	-26
	<110	-4	-5	-8	-10	-13	-18	-23	-26



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>W</sub>I sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	ΔP stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<50	-5	-8	-6	-6	-6	-12	-20	-27
	<85	-4	-5	-5	-5	-8	-16	-23	-30
25°	<50	-4	-5	-7	-9	-13	-19	-24	-30
	<85	5	-7	-4	-7	-11	-17	-23	-29
40°	<50	-4	-5	-8	-10	-14	-20	-23	-26
	<70	-4	-5	-8	-10	-13	-18	-23	-26



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>W</sub>I sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
10°	<1000	-8	-5	-15	-9	-6	-6	-8	-13
	<2000	-6	-3	-15	-6	-6	-7	-9	-14
20°	<1000	-7	-4	-14	-9	-9	-9	-11	-17
	<1800	-8	-5	-15	-6	-5	-7	-11	-17
30°	<1000	-6	-3	-13	-9	-9	-12	-15	-20
	<1600	-6	-4	-13	-9	-7	-9	-13	-18
40°	<1000	-6	-3	-13	-10	-10	-13	-17	-23
	<1600	-6	-3	-14	-10	-11	-12	-16	-22

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013 \text{ hPa}$





- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


Axial Fan  
Hub : 250mm

**Matthews & Yates** Division




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<250	-4	-14	-8	-6	-6	-8	-13	-19
	<500	-2	-13	-6	-5	-7	-11	-17	-25
20°	<250	-3	-13	-9	-5	-8	-10	-16	-22
	<450	-3	-14	-6	-5	-7	-11	-17	-25
30°	<250	-3	-12	-8	-8	-11	-15	-19	-24
	<400	-2	-12	-8	-6	-8	-12	-17	-23
40°	<250	-2	-12	-9	-9	-12	-16	-22	-28
	<400	-2	-12	-9	-9	-11	-15	-21	-26



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.


Inlet Levels									
Pitch Angle	$\Delta p_{stat}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<120	-9	-9	-6	-5	-6	-10	-15	-21
	<220	-5	-7	-5	-5	-9	-14	-21	-28
20°	<120	-7	-8	-5	-5	-8	-12	-18	-22
	<200	-9	-10	-4	-5	-8	-12	-19	-26
30°	<120	-6	-8	-5	-8	-10	-14	-19	-23
	<180	-6	-8	-5	-6	-9	-14	-19	-23
40°	<120	-5	-8	-6	-8	-12	-17	-23	-28
	<180	-5	-8	-6	-8	-11	-16	-22	-27



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Inlet Levels									
Pitch Angle	ΔP stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<50	-12	-7	-6	-5	-7	-11	-17	-23
	<130	-8	-4	-4	-6	-7	-12	-20	-29
20°	<50	-10	-5	-4	-7	-9	-15	-19	-23
	<120	-8	-4	-4	-6	-10	-16	-24	-28
30°	<50	-9	-5	-5	-7	-11	-15	-20	-25
	<110	-9	-6	-5	-6	-10	-15	-19	-23
40°	<50	-8	-5	-5	-8	-12	-18	-24	-29
	<100	-8	-5	-5	-7	-11	-17	-22	-27



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA


Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{stat}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<200	-11	-6	-8	-4	-6	-6	-12	-19
	<350	-12	-5	-7	-2	-7	-10	-15	-20
25°	<200	-8	-6	-6	-8	-9	-13	-17	-21
	<350	-10	-7	-5	-4	-6	-11	-17	-22
40°	<200	-8	-6	-6	-8	-9	-13	-18	-21
	<260	-8	-5	-5	-8	-9	-13	-18	-21



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.

AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013\text{hPa}$





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<90	-8	-5	-7	-6	-6	-12	-16	-21
	<160	-8	-4	-5	-4	-8	-13	-18	-24
25°	<90	-6	-4	-7	-8	-11	-15	-19	-23
	<160	-8	-6	-4	-5	-9	-14	-19	-23
40°	<90	-6	-5	-7	-8	-11	-15	-19	-22
	<120	-7	-4	-7	-8	-11	-15	-19	-22



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta p$ stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<50	-5	-7	-5	-6	-6	-12	-18	-23
	<90	-5	-6	-3	-7	-8	-14	-20	-25
25°	<50	-5	-5	-7	-8	-12	-16	-20	-24
	<90	-6	-5	-4	-6	-11	-17	-20	-24
40°	<50	-5	-5	-7	-8	-12	-17	-20	-24
	<70	-5	-5	-7	-8	-12	-17	-20	-23



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
Hub : 250mm



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P$ stat. [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<300	-8	-14	-8	-6	-5	-6	-12	-16
	<600	-8	-10	-4	-4	-8	-8	-15	-21
20°	<300	-7	-11	-6	-6	-6	-8	-14	-19
	<600	-7	-11	-3	-7	-6	-8	-14	-19
30°	<300	-5	-10	-6	-6	-8	-11	-15	-20
	<450	-7	-12	-6	-4	-7	-11	-15	-20
40°	<300	-5	-11	-7	-7	-9	-12	-16	-21
	<400	-6	-11	-7	-6	-8	-11	-15	-20



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<140	-11	-10	-6	-5	-5	-9	-13	-17
	<270	-9	-7	-3	-6	-6	-10	-17	-24
20°	<140	-9	-8	-5	-5	-7	-11	-16	-21
	<250	-10	-7	-3	-5	-7	-11	-16	-21
30°	<140	-8	-7	-5	-7	-10	-13	-18	-23
	<210	-9	-8	-5	-5	-9	-13	-18	-23
40°	<140	-7	-8	-5	-7	-9	-13	-17	-22
	<180	-8	-8	-5	-7	-9	-13	-17	-22



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{stat}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<80	-13	-6	-5	-5	-6	-11	-15	-19
	<160	-9	-4	-4	-6	-8	-12	-19	-25
20°	<80	-10	-6	-4	-5	-8	-13	-18	-23
	<140	-10	-2	-6	-5	-8	-23	-28	-23
30°	<80	-9	-5	-5	-7	-10	-14	-19	-24
	<125	-10	-6	-4	-6	-10	-14	-19	-24
40°	<80	-9	-5	-5	-7	-10	-14	-19	-24
	<110	-10	-6	-5	-7	-10	-14	-19	-24



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


Axial Fan  
Hub : 350mm




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<300	-14	-6	-8	-6	-4	-10	-15	-18
	<550	-14	-4	-6	-5	-4	-11	-18	-22
25°	<300	-10	-3	-8	-7	-11	-16	-20	-25
	<550	-10	-4	-7	-3	-8	-14	-18	-23
40°	<300	-6	-4	-8	-9	-12	-17	-21	-24
	<400	-6	-4	-8	-10	-13	-17	-21	-24



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<130	-9	-7	-7	-4	-7	-13	-17	-20
	<240	-8	-4	-6	-4	-7	-14	-20	-24
25°	<130	-5	-4	-8	-9	-13	-18	-22	-26
	<240	-6	-4	-4	-5	-11	-16	-20	-25
40°	<130	-4	-5	-8	-10	-14	-18	-22	-25
	<180	-4	-5	-8	-11	-14	-18	-22	-25



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA



Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
	<80	-8	-8	-6	-3	-9	-15	-18	-21
10°	<140	-4	-5	-5	-4	-11	-18	-23	-28
	<80	-3	-6	-7	-10	-16	-20	-24	-28
25°	<140	-4	-7	-3	-8	-14	-18	-23	-28
	<80	-3	-7	-8	-10	-15	-19	-22	-25
40°	<110	-3	-6	-9	-11	-15	-19	-22	-25



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	ΔP stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<350	-9	-13	-9	-6	-4	-10	-15	-20
	<650	-6	-8	-5	-6	-5	-12	-17	-24
25°	<350	-5	-7	-6	-8	-11	-16	-19	-24
	<650	-6	-7	-7	-4	-8	-12	-17	-23
40°	<350	-5	-7	-7	-8	-11	-16	-22	-25
	<480	-5	-3	-7	-8	-10	-15	-21	-24



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta p$ stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<150	-10	-9	-7	-4	-7	-12	-17	-22
	<300	-6	-5	-6	-4	-8	-15	-21	-27
25°	<150	-5	-6	-6	-9	-13	-17	-21	-26
	<300	-6	-7	-5	-6	-10	-14	-20	-26
40°	<150	-5	-7	-6	-8	-13	-18	-23	-25
	<220	-3	-7	-7	-8	-12	-17	-22	-25



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-15}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<80	-12	-8	-6	-3	-9	-14	-19	-24
	<170	-6	-3	-5	-4	-11	-17	-23	-28
25°	<80	-6	-4	-6	-9	-15	-18	-22	-27
	<170	-6	-5	-4	-7	-11	-16	-22	-27
40°	<80	-6	-5	-6	-8	-14	-20	-23	-25
	<120	-2	-6	-7	-9	-14	-20	-23	-26



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


 Axial Fan  
 Hub : 350mm




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<400	-7	-15	-5	-7	-6	-10	-16	-21
	<850	-6	-13	-3	-4	-7	-11	-18	-25
20°	<400	-5	-12	-5	-8	-9	-15	-19	-25
	<600	-6	-13	-5	-3	-7	-13	-19	-25
30°	<400	-4	-12	-5	-8	-11	-17	-23	-27
	<720	-6	-11	-4	-6	-8	-14	-19	-23
40°	<400	-5	-5	-8	-8	-11	-25	-20	-24
	<650	-6	-5	-8	-8	-10	-14	-20	-23



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


Axial Fan  
Hub : 350mm




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta P_{stat}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<200	-11	-8	-4	-5	-7	-13	-18	-23
	<400	-9	-6	-4	-5	-8	-14	-21	-26
20°	<200	-8	-6	-4	-7	-11	-16	-22	-26
	<300	-9	-7	-5	-10	-16	-22	-28	
30°	<200	-7	-6	-4	-8	-13	-19	-24	-28
	<300	-8	-6	-4	-7	-11	-16	21	-25
40°	<200	-4	-8	-7	-9	-12	-18	-23	-26
	<300	-4	-8	-7	-9	-12	-18	-22	-25



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{stat}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<120	-14	-4	-5	-5	-9	-15	-20	-25
	<230	-12	-2	-4	-6	-10	-17	-24	-28
20°	<120	-10	-3	-5	-8	-13	-18	-23	-27
	<180	-12	-4	-3	-7	-13	-18	-24	-30
30°	<120	-10	-3	-6	-9	-15	-21	-25	-29
	<200	-10	-4	-5	-7	-13	-18	-22	-26
40°	<120	-4	-7	-6	-9	-14	-19	-24	-26
	<180	-4	-7	-7	-9	-13	-18	-22	-25



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<300	-15	-12	-9	-4	-4	-9	-14	-16
	<550	-14	-5	-4	-3	-6	-13	-17	-19
25°	<300	-5	-5	-7	-8	-11	-16	-20	-19
	<550	-6	-6	-7	-3	-6	-13	-18	-22
40°	<200	-5	-5	-6	-10	-12	-16	-20	-23
	<370	-7	-4	-5	-11	-13	-17	-21	-25



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	ΔP stat. [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<150	-13	-9	-5	-4	-7	-11	-14	-16
	<220	-9	-4	-5	-4	-10	-16	-19	-20
25°	<150	-5	-5	-7	-9	-13	-17	-19	-18
	<220	-6	-7	-4	-5	-9	-15	-20	-24
40°	<100	-2	-3	-9	-10	-14	-19	-22	-25
	<170	-6	-3	-10	-11	-15	-20	-24	-28



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-15</sup> watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<80	-12	-8	-5	-4	-9	-13	-15	-17
	<140	-6	-4	-3	-6	-11	-16	-18	-20
25°	<80	-4	-6	-7	-9	-14	-18	-18	-17
	<140	-4	-7	-3	-5	-12	-17	-21	-25
40°	<60	-4	-5	-8	-10	-15	-19	-22	-25
	<100	-4	-4	-10	-12	-16	-20	-24	-28



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta p_{\text{stat.}}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<400	-13	-15	-6	-6	-3	-9	-12	-16
	<700	-9	-9	-3	-5	-6	-12	-16	-19
25°	<400	-5	-10	-5	-7	-8	-11	-15	-17
	<700	-9	-11	-5	-3	-6	-11	-16	-20
40°	<300	-4	-5	-6	-10	-12	-16	-22	-26
	<500	-5	-4	-3	-12	-14	-18	-24	-29



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
  - The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

		Inlet Levels							
Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<180	-14	-7	-6	-4	-7	-10	-14	-18
	<300	-9	-5	-5	-6	-10	-14	-17	-20
25°	<180	-8	-5	-6	-7	-9	-12	16	-17
	<300	-9	-8	-3	-4	-8	-13	-17	-21
40°	<130	-2	-2	-9	-11	-14	-20	-25	-28
	<220	-3	-1	-13	-14	-17	-23	-29	-34



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<100	-14	-5	-5	-3	-8	-11	-15	-19
	<180	-9	-3	-5	-6	-11	-15	-18	-21
25°	<100	-9	-4	-6	-7	-10	-14	-16	-17
	<180	-10	-6	-3	-5	-11	-15	-19	-23
40°	<80	-3	-4	-8	-10	-14	-20	-24	-27
	<120	-3	-2	-11	-12	-16	-21	-25	-28

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ \text{C}$ ,  $1013 \text{ hPa}$ 


- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p$ stat. [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<500	-14	-18	-2	-5	-5	-10	-14	-17
	<800	-14	-19	-2	-5	-6	-12	-18	-22
20°	<500	-9	-16	-6	-5	-5	-9	-13	-17
	<800	-12	-19	-9	-2	-5	-10	-16	-23
30°	<500	-4	-15	-5	-6	-9	-12	-17	-21
	<800	-7	-15	-6	-3	-7	-13	-18	-23
40°	<500	-4	-6	-9	-7	-9	-13	-19	-22
	<750	-6	-6	-8	-7	-9	-13	-18	-22



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



Pitch Angle	ΔP stat. [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<250	-16	-8	-3	-4	-7	-12	-15	-18
	<350	-16	-8	-3	-5	-9	-15	-19	-23
20°	<250	-13	-9	-5	-4	-6	-11	-15	-18
	<350	-16	-13	-5	-3	-7	-14	-20	-26
30°	<250	-8	-7	-4	-6	-9	-13	-18	-21
	<350	-11	-9	-4	-4	-9	-14	-20	-24
40°	<250	-2	-10	-6	-8	-11	-17	-21	-23
	<320	-4	-8	-6	-8	-11	-15	-21	-23



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA



Single figure on performance curves are overall inlet L<sub>W</sub>I sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Inlet Levels										
Pitch Angle	$\Delta p_{\text{stat.}}$ [Pa]	Octave Band Centre Frequency (Hz)								AMCA Worldwide Certified Ratings
		63	125	250	500	1K	2K	4K	8K	
10°	<130	-17	-2	-5	-4	-9	-13	-16	-19	SOUND AND AIR PERFORMANCE
	<210	-18	-2	-5	-6	-12	-17	-21	-25	
20°	<130	-16	-5	-5	-4	-8	-13	-16	-19	AMCA INTERNATIONAL STANDARD 301
	<210	-19	-9	-2	-5	-10	-16	-22	-26	
30°	<130	-13	-3	-5	-7	-10	-15	-19	-22	Values shown are for inlet L <sub>W</sub> I sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.
	<210	-15	-6	-3	-7	-11	-17	-21	-24	
40°	<130	-3	-8	-6	-8	-12	-17	-22	-24	Ratings include the effects of duct end correction.
	<180	-5	-7	-6	-8	-12	-17	-21	-23	



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>W</sub>I sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet Lwi sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P$ stat. [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<300	-12	-10	-6	-5	-6	-8	-12	-17
	<500	-4	-6	-5	-6	-8	-12	-16	-20
25°	<300	-6	-6	-6	-8	-9	-13	-18	-21
	<700	-8	-7	-6	-4	-7	-11	-16	-21
40°	<250	-6	-3	-9	-11	-13	-17	-21	-26
	<400	-6	-3	-9	-13	-16	-19	-24	-29



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA



Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{stat}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<150	-10	-8	-5	-5	-6	-11	-12	-23
	<250	-3	-5	-5	-8	-10	-16	-16	-26
25°	<150	-4	-5	-7	-7	-11	-16	-18	-25
	<300	-6	-6	-4	-5	-9	-14	-19	-24
40°	<110	-3	-5	-10	-12	-15	-19	-23	-27
	<180	-3	-4	-11	-16	-21	-21	-26	-30

AMCA 210, ISO 5801:2007 -  $p = 1.2\text{kg/m}^3, 20^\circ\text{C}, 1013\text{hPa}$



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<80	-9	-6	-5	-5	-8	-11	-16	-27
	<130	-4	-5	-6	-8	-12	-15	-19	-27
25°	<80	-5	-5	-7	-8	-12	-17	-20	-26
	<180	-6	-6	-4	-6	-10	-15	-20	-25
40°	<60	-1	-7	-10	-12	-15	-20	-25	-28
	<100	-1	-8	-12	-14	-17	-23	-27	-32



- Performance certified for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<400	-11	-9	-5	-4	-5	-8	-12	-17
	<700	-7	-6	-4	-6	-9	-11	-13	-18
25°	<400	-6	-6	-9	-7	-9	-11	-15	-19
	<800	-7	-7	-9	-4	-6	-9	-13	-20
40°	<300	-6	-3	-9	-10	-12	-15	-21	-26
	<500	-6	-3	-8	-11	-13	-16	-22	-28



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Inlet Levels							
		63	125	250	500	1K	2K	4K	8K
10°	<200	-10	-5	-4	-5	-7	-12	-13	-23
10°	<300	-5	-5	-6	-9	-10	-12	-13	-23
25°	<200	-4	-9	-6	-8	-9	-12	-16	-23
25°	<350	-6	-10	-5	-5	-8	-10	-16	-24
40°	<140	-3	-7	-9	-10	-13	-17	-22	-27
40°	<220	-3	-6	-9	-11	-14	-18	-24	-29



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.




### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{stat.}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<120	-9	-4	-4	-5	-8	-12	-16	-27
	<180	-5	-4	-6	-9	-10	-12	-16	-26
25°	<120	-5	-8	-6	-8	-10	-13	-18	-24
	<220	-6	-9	-4	-5	-9	-12	-19	-26
40°	<80	-2	-8	-9	-10	-14	-19	-24	-29
	<130	-2	-7	-10	-12	-15	-21	-26	-30



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-1}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



Inlet Levels										
Pitch Angle	ΔP stat. [Pa]	Octave Band Centre Frequency (Hz)								
		63	125	250	500	1K	2K	4K	8K	
10°	<500	-14	-12	-9	-5	-5	-7	-11	-16	
	<1000	-13	-8	-6	-4	-6	-9	-14	-18	
20°	<500	-10	-9	-8	-5	-6	-8	-13	-17	
	<1000	-13	-11	-7	-5	-6	-8	-13	-19	
30°	<500	-5	-7	-8	-6	-10	-13	-17	-22	
	<950	-7	-8	-7	-5	-7	-11	-16	-21	
40°	<500	-5	-3	-10	-12	-13	-16	-21	-26	
	<800	-6	-4	-9	-10	-11	-14	-19	-24	



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to 10<sup>-12</sup> watts, calculated per AMCA International Standard 301.

Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.





### SOUND DATA

Single figure on performance curves are overall inlet L<sub>WI</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{stat}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<250	-13	-12	-6	-5	-6	-10	-12	-21
	<450	-12	-5	-4	-6	-8	-12	-16	-22
20°	<250	-8	-12	-5	-6	-6	-11	-15	-22
	<450	-13	-10	-4	-5	-8	-12	-18	-24
30°	<250	-5	-11	-5	-8	-12	-15	-19	-25
	<420	-6	-10	-5	-5	-8	-14	-18	-24
40°	<250	-2	-6	-8	-10	-13	-17	-22	-26
	<350	-4	-6	-8	-10	-12	-16	-21	-26



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.
- Values shown are for inlet L<sub>WI</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


Axial Fan  
Hub : 350mm



### SOUND DATA

Single figure on performance curves are overall inlet L<sub>wi</sub> sound power levels, derived from measurements taken in laboratory specifically under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta p_{\text{stat}}$ [Pa]	Inlet Levels							
		Octave Band Centre Frequency (Hz)							
		63	125	250	500	1K	2K	4K	8K
10°	<150	-12	-8	-5	-5	-7	-11	-15	-24
	<280	-9	-5	-4	-6	-9	-13	-18	-24
20°	<150	-9	-8	-5	-6	-7	-12	-17	-24
	<280	-10	-7	-4	-6	-9	-14	-19	-26
30°	<150	-5	-7	-5	-8	-12	-16	-20	-26
	<250	-7	-7	-4	-6	-10	-15	-19	-25
40°	<150	-1	-8	-10	-11	-14	-19	-24	-28
	<200	-3	-8	-9	-10	-13	-18	-23	-28

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013 \text{ hPa}$ 


- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for inlet L<sub>wi</sub> sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.


Axial Fan  
Hub : 500mm


### SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



Pitch Angle	$\Delta P_{\text{Stat}}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-5	-5	-12	-12	-11	-8	-15	-16
	215	-5	-5	-12	-13	-12	-9	-15	-16
	507	-8	-8	-14	-5	-8	-8	-16	-21
22°	0	-3	-3	-15	-17	-19	-17	-23	-24
	238	-3	-4	-14	-18	-20	-17	-22	-24
	649	-5	-3	-16	-17	-16	-15	-19	-21
30°	0	-4	-4	-14	-17	-17	-14	-20	-21
	472	-4	-3	-14	-17	-17	-13	-16	-20
	699	-5	-4	-15	-16	-15	-12	-15	-19
36°	0	-4	-4	-15	-17	-18	-15	-16	-21
	265	-4	-3	-15	-16	-17	-13	-16	-20
	480	-5	-5	-9	-12	-14	-14	-20	-24

AMCA 210, ISO 5801:2007 -  $p = 1.2\text{kg/m}^3$ ,  $20^\circ\text{C}$ , 1013hPa


- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)
- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for outlet Lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 67

    
Axial Fan  
Hub : 500mm



## SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{stat}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-5	-5	-12	-11	-9	-12	-15	-21
	97	-5	-5	-12	-12	-10	-12	-15	-21
22°	0	-3	-3	-16	-18	-18	-21	-23	-26
	229	-7	-7	-8	-6	-7	-12	-19	-25
30°	0	-3	-3	-16	-18	-18	-21	-23	-26
	108	-3	-4	-16	-19	-18	-20	-23	-26
36°	0	-4	-4	-16	-16	-15	-17	-20	-22
	293	-5	-3	-16	-16	-15	-17	-20	-22
36°	0	-4	-4	-15	-17	-15	-17	-20	-22
	214	-4	-3	-16	-17	-15	-16	-19	-21
36°	316	-4	-3	-15	-16	-13	-13	-17	-20
	0	-4	-4	-16	-17	-16	-15	-19	-22
36°	120	-4	-3	-16	-17	-15	-15	-19	-22
	217	-4	-5	-10	-12	-13	-16	-21	-25





• Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

• The sound power level ratings shown are in decibels, referred to 10<sup>-2</sup>watts, calculated per AMCA International Standard 301.

Values shown are for outlet Lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

**FEG 67**



## SOUND DATA



Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
12°	0	-4	-11	-11	-10	-7	-14	-14	-24
	56	-3	-10	-11	-10	-7	-13	-14	-23
	132	-7	-13	-4	-7	-7	-15	-20	-27
	185	-9	-6	-3	-11	-13	-20	-23	-29
22°	0	-1	-12	-14	-17	-14	-21	-21	-25
	62	-1	-12	-16	-18	-15	-20	-22	-25
	169	-1	-12	-13	-12	-11	-15	-17	-20
	207	-6	-4	-7	-11	-14	-21	-24	-29
30°	0	-1	-11	-14	-14	-11	-17	-18	-20
	123	-2	-12	-15	-15	-11	-14	-18	-19
36°	0	-1	-12	-14	-15	-12	-13	-18	-20
	69	-2	-13	-14	-15	-11	-14	-18	-21
	125	-3	-7	-10	-12	-12	-18	-22	-26



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).
- The sound power level ratings shown are in decibels, referred to 10<sup>-2</sup> watts, calculated per AMCA International Standard 301. Values shown are for outlet Lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction.

**FEG 67**


Axial Fan  
Hub : 500mm


## SOUND DATA

Single figure on performance curves are over all outlet lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



Pitch Angle	ΔP Stat. (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-7	-7	-10	-10	-8	-7	-11	-14
	445	-9	-9	-12	-8	-7	-7	-14	-18
	799	-9	-9	-6	-6	-9	-11	-18	-23
22°	0	-4	-4	-10	-14	-16	-11	-18	-16
	326	-4	-5	-10	-14	-14	-11	-16	-19
	607	-5	-5	-12	-11	-11	-10	-15	-18
30°	0	-4	-4	-12	-15	-17	-15	-20	-21
	349	-4	-4	-11	-15	-16	-13	-17	-20
	875	-5	-5	-11	-12	-12	-12	-16	-20
36°	0	-4	-4	-12	-15	-16	-13	-17	-20
	415	-4	-4	-11	-14	-14	-12	-15	-19
	653	-3	-3	-14	-17	-19	-20	-25	-30



• Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)

• The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for outlet lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 67


Axial Fan  
Hub : 500mm


## SOUND DATA

Single figure on performance curves are over all outlet lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



Pitch Angle	ΔP Stat. (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-7	-8	-10	-8	-7	-9	-12	-19
	201	-8	-10	-9	-6	-6	-10	-15	-22
	361	-8	-7	-5	-7	-10	-15	-20	-27
22°	0	-3	-6	-11	-14	-12	-14	-17	-22
	148	-3	-7	-12	-13	-11	-13	-16	-21
	274	-4	-8	-10	-10	-9	-12	-16	-20
30°	0	-2	-7	-12	-14	-14	-16	-19	-21
	158	-2	-7	-12	-14	-13	-14	-17	-20
	396	-3	-7	-10	-10	-10	-13	-17	-21
36°	0	-2	-7	-12	-14	-13	-14	-17	-20
	187	-3	-7	-12	-13	-11	-12	-16	-19
	295	-1	-8	-14	-16	-18	-21	-26	-32



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for outlet lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 67


Axial Fan  
Hub : 500mm


## SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{stat}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-6	-9	-9	-7	-6	-10	-12	-23
	116	-8	-12	-7	-6	-6	-13	-17	-26
	208	-8	-5	-5	-8	-10	-17	-22	-30
	264	-3	-6	-11	-14	-13	-20	-23	-29
22°	0	-2	-8	-12	-14	-9	-16	-16	-24
	85	-2	-9	-12	-12	-8	-14	-16	-22
	158	-3	-10	-9	-9	-8	-13	-16	-21
	249	-1	-9	-15	-19	-19	-26	-31	-37
30°	0	-2	-10	-13	-15	-13	-18	-19	-22
	91	-2	-10	-13	-14	-11	-15	-18	-20
36°	0	-2	-10	-13	-14	-11	-15	-18	-21
	108	-2	-10	-12	-12	-10	-13	-17	-20
	170	-1	-12	-15	-17	-18	-23	-28	-34

AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ , 20°C, 1013hPa


• Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)

• The sound power level ratings shown are in decibels, referred to 10<sup>-2</sup>watts, calculated per AMCA International Standard 301.



Values shown are for outlet Lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 67



Axial Fan

Hub : 500mm



### SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{\text{Stat.}}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-10	-10	-10	-9	-8	-7	-10	-13
	591	-13	-13	-12	-7	-6	-6	-12	-17
	987	-9	-9	-8	-5	-7	-10	-16	-22
22°	0	-4	-4	-12	-15	-17	-14	-22	-22
	783	-7	-7	-9	-7	-8	-9	-14	-18
	1033	-7	-7	-7	-7	-12	-14	-20	-26
30°	0	-4	-4	-11	-14	-16	-15	-21	-23
	468	-5	-5	-9	-14	-14	-13	-18	-20
	857	-5	-5	-10	-13	-12	-11	-15	-17
36°	0	-4	-4	-13	-16	-17	-15	-21	-22
	392	-4	-4	-11	-15	-16	-12	-18	-20
	799	-4	-4	-12	-15	-14	-12	-17	-19




AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ , 20°C, 1013hPa


• Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)

• The sound power level ratings shown are in decibels, referred to 10<sup>-2</sup>watts, calculated per AMCA International Standard 301.

Values shown are for outlet Lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 60


Axial Fan  
Hub : 500mm


### SOUND DATA

Single figure on performance curves are over all outlet lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{Stat}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-9	-9	-9	-8	-7	-8	-11	-19
	267	-12	-13	-9	-6	-5	-9	-14	-22
	446	-9	-8	-6	-6	-9	-13	-19	-26
22°	0	-2	-7	-10	-14	-13	-17	-20	-24
	354	-7	-9	-8	-7	-8	-11	-15	-20
	467	-6	-6	-6	-9	-12	-16	-22	-28
30°	0	-3	-7	-10	-14	-14	-17	-21	-24
	212	-3	-7	-7	-13	-12	-14	-18	-21
	378	-4	-7	-9	-11	-10	-12	-15	-18
36°	0	-2	-7	-11	-15	-14	-17	-20	-22
	177	-3	-7	-10	-14	-12	-14	-18	-20
	361	-3	-8	-11	-13	-11	-14	-17	-19





• Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)

• The sound power level ratings shown are in decibels, referred to to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for outlet lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 60


Axial Fan  
Hub : 500mm


### SOUND DATA

Single figure on performance curves are over all inlet Lwi sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{Stat.}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-9	-9	-9	-7	-6	-9	-12	-23
	154	-12	-13	-6	-5	-5	-11	-16	-26
	257	-9	-8	-5	-7	-10	-16	-22	-29
	327	-8	-3	-9	-12	-12	-19	-22	-28
22°	0	-2	-10	-13	-15	-12	-20	-20	-26
	204	-6	-10	-6	-7	-7	-12	-16	-21
	269	-6	-6	-6	-11	-13	-19	-25	-31
	290	-3	-5	-13	-16	-17	-23	-28	-35
30°	0	-2	-9	-12	-14	-13	-19	-21	-25
	122	-2	-8	-11	-12	-10	-15	-17	-21
	0	-1	-10	-13	-14	-12	-18	-19	-22
	102	-2	-10	-13	-14	-10	-16	-18	-20
36°	208	-2	-11	-13	-12	-10	-15	-17	-20





• Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)

• The sound power level ratings shown are in decibels, referred to  $10^{12}$  watts, calculated per AMCA International Standard 301.

Values shown are for outlet Lwi sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 60


Axial Fan  
Hub : 500mm


## SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP Stat. (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-5	-5	-8	-13	-13	-13	-15	-14
	426	-8	-7	-14	-8	-7	-8	-14	-17
	737	-11	-11	-10	-2	-9	-13	-18	-21
22°	0	-4	-4	-11	-13	-17	-18	-21	-19
	538	-4	-4	-10	-12	-12	-14	-16	-18
	741	-7	-7	-10	-5	-8	-12	-16	-19
30°	0	-4	-4	-11	-15	-17	-16	-18	-18
	299	-4	-4	-12	-16	-17	-15	-17	-17
	568	-5	-4	-9	-11	-11	-13	-15	-18

AMCA 210, ISO 5801:2007 -  $\rho = 1.2 \text{ kg/m}^3$ ,  $20^\circ\text{C}$ ,  $1013\text{hPa}$ 


- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

The sound power level ratings shown are in decibels, referred to  $10^{-2} \text{ watts}$ , calculated per AMCA International Standard 301.



Values shown are for outlet Lwo sound power levels for installation type D; ducted inlet, ducted outlet. Ratings include the effects of duct end correction

**FEG 71**



Axial Fan

Hub : 500mm



### SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{Stat}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-5	-5	-11	-13	-13	-14	-14	-18
	193	-8	-7	-10	-7	-7	-11	-15	-21
	333	-10	-10	-4	-5	-11	-15	-19	-23
22°	0	-4	-4	-12	-15	-17	-19	-19	-20
	243	-4	-4	-11	-12	-13	-15	-17	-19
	335	-7	-7	-7	-7	-10	-14	-18	-21
30°	0	-4	-4	-13	-16	-16	-17	-18	-20
	135	-4	-4	-14	-16	-16	-16	-17	-19
	257	-5	-4	-10	-11	-12	-14	-16	-20



AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ , 20°C, 1013hPa


• Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

• The sound power level ratings shown are in decibels, referred to 10<sup>-2</sup>watts, calculated per AMCA International Standard 301.

Values shown are for outlet Lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 71


Axial Fan  
Hub : 500mm


## SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP Stat. (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-4	-6	-11	-11	-11	-14	-12	-20
	111	-7	-12	-7	-6	-7	-13	-16	-23
	192	-11	-10	-2	-9	-13	-18	-21	-26
	239	-1	-10	-12	-15	-17	-21	-23	-27
22°	0	-2	-9	-11	-15	-16	-19	-17	-20
	140	-3	-9	-11	-11	-13	-15	-16	-19
	193	-6	-9	-4	-7	-11	-15	-18	-22
	215	-6	-4	-7	-10	-14	-19	-23	-28
30°	0	-2	-9	-13	-15	-14	-16	-16	-19
	78	-2	-10	-14	-15	-13	-15	-15	-19
	148	-4	-8	-10	-10	-12	-14	-16	-20
	183	-5	-4	-10	-13	-16	-21	-26	-31





• Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

• The sound power level ratings shown are in decibels, referred to 10<sup>-2</sup>watts, calculated per AMCA International Standard 301.

Values shown are for outlet lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

**FEG 71**


Axial Fan  
Hub : 500mm


### SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P$ Stat. (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-7	-7	-8	-12	-10	-9	-11	-12
	284	-9	-9	-8	-10	-8	-6	-10	-14
	763	-10	-10	-12	-4	-6	-9	-15	-20
22°	0	-4	-4	-10	-12	-16	-16	-19	-20
	718	-6	-6	-11	-9	-8	-11	-15	-18
	968	-8	-8	-11	-5	-7	-11	-16	-20
30°	276	-4	-4	-11	-12	-15	-17	-19	-20
	622	-4	-4	-10	-12	-13	-14	-16	-18
	902	-5	-5	-12	-12	-11	-13	-16	-19



AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ , 20°C, 1013hPa


- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

- The sound power level ratings shown are in decibels, referred to  $10^{12}$  watts, calculated per AMCA International Standard 301.

Values shown are for outlet lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 67


Axial Fan  
Hub : 500mm


## SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



Pitch Angle	$\Delta P$ Stat. (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-6	-7	-10	-10	-9	-9	-11	-17
	128	-9	-8	-9	-9	-7	-8	-12	-18
	354	-10	-11	-7	-5	-7	-12	-17	-23
22°	0	-3	-6	-10	-13	-15	-17	-18	-21
	325	-5	-9	-9	-7	-9	-12	-16	-20
	437	-7	-9	-7	-6	-9	-13	-18	-22
30°	125	-3	-7	-10	-12	-15	-17	-18	-20
	281	-3	-7	-10	-12	-13	-14	-16	-18
	408	-3	-8	-11	-10	-10	-13	-16	-19



- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301. Values shown are for outlet Lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 67


 Axial Fan  
 Hub : 500mm


### SOUND DATA

Single figure on performance curves are over all outlet lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{Stat.}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-6	-7	-11	-9	-8	-10	-11	-20
	74	-9	-9	-10	-8	-6	-10	-13	-22
	204	-10	-12	-4	-6	-9	-15	-19	-27
	320	-2	-7	-12	-14	-15	-19	-23	-27
22°	0	-2	-8	-10	-14	-14	-17	-18	-22
	187	-5	-11	-8	-7	-10	-14	-17	-22
	252	-7	-10	-4	-6	-10	-15	-19	-24
	277	-6	-4	-6	-10	-13	-18	-23	-28
30°	72	-2	-9	-10	-13	-15	-17	-18	-20
	162	-2	-8	-10	-11	-12	-14	-16	-18
	235	-3	-11	-10	-9	-11	-14	-17	-20
	274	-4	-7	-8	-10	-13	-18	-23	-28





- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)

- The sound power level ratings shown are in decibels, referred to  $10^{-12}$  watts, calculated per AMCA International Standard 301.

Values shown are for outlet lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

**FEG 67**


Axial Fan  
Hub : 500mm


## SOUND DATA



Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	ΔP stat. (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-8	-8	-7	-12	-9	-9	-11	-11
	415	-12	-12	-10	-6	-5	-7	-13	-18
	1202	-12	-12	-6	-5	-7	-11	-16	-21
22°	0	-5	-5	-8	-14	-16	-16	-19	-19
	476	-6	-6	-7	-12	-11	-12	-15	-17
	868	-10	-10	-11	-5	-7	-9	-13	-18
30°	334	-5	-5	-8	-13	-15	-16	-18	-18
	837	-5	-5	-7	-13	-13	-14	-15	-17
	1163	-6	-6	-9	-9	-9	-12	-14	-17

AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ , 20°C, 1013hPa


- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)
- The sound power level ratings shown are in decibels, referred to  $10^{-2}$  watts, calculated per AMCA International Standard 301. Values shown are for outlet Lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 71


Axial Fan  
Hub : 500mm


## SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.



Pitch Angle	$\Delta P_{Stat.}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-8	-7	-7	-10	-9	-10	-11	-17
	187	-12	-11	-8	-5	-6	-10	-15	-23
22°	543	-12	-8	-5	-6	-9	-14	-19	-25
	0	-4	-6	-7	-14	-15	-17	-18	-21
30°	215	-5	-7	-6	-11	-11	-13	-15	-19
	392	-9	-10	-7	-6	-8	-11	-15	-20
	151	-4	-6	-7	-13	-15	-16	-17	-19
	378	-4	-6	-8	-12	-13	-14	-16	-18
	526	-5	-7	-8	-8	-10	-12	-15	-18

AMCA 210, ISO 5801:2007 -  $\rho = 1.2\text{kg/m}^3$ , 20°C, 1013hPa


- Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories)
- The sound power level ratings shown are in decibels, referred to  $10^{-2}$  watts, calculated per AMCA International Standard 301. Values shown are for outlet Lwo sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction

FEG 71

AXC (A) 1600-12-8, 50Hz 740 rpm


 Axial Fan  
Hub : 500mm


### SOUND DATA

Single figure on performance curves are over all outlet Lwo sound power levels, derived from measurements taken specifically in the laboratory under ducted conditions. For sound power levels in eight octave bands, apply the following corrections to the overall levels.

Pitch Angle	$\Delta P_{Stat}$ (Pa)	Octave Band Centre Frequency (Hz)							
		63	125	250	500	1000	2000	4000	8000
10°	0	-7	-6	-11	-8	-8	-10	-10	-21
	108	-12	-11	-6	-5	-7	-13	-17	-27
	313	-12	-6	-5	-7	-11	-16	-21	-28
22°	0	-9	-3	-8	-11	-13	-16	-19	-24
	124	-3	-6	-12	-14	-14	-17	-17	-22
	226	-4	-7	-10	-9	-10	-13	-15	-20
	340	-10	-11	-5	-7	-9	-13	-18	-23
30°	0	-2	-5	-11	-14	-16	-21	-26	-33
	87	-3	-6	-11	-13	-14	-16	-16	-20
	218	-3	-6	-11	-11	-12	-13	-15	-18
	303	-5	-8	-8	-8	-11	-13	-16	-19
	334	-7	-8	-5	-8	-12	-15	-20	-25




\* Performance certified is for installation type D - Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (Accessories).

\* The sound power level ratings shown are in decibels, referred to  $10^{-2}$  walls, calculated per AMCA International Standard 301.

Values shown are for outlet Lwo sound power levels for installation type D, ducted inlet, ducted outlet. Ratings include the effects of duct end correction.

FEG 71



Fan dimension	Motor frame size (min.)	Motor frame size (max.)	$\phi D_i$	$\phi D_a$	$s$	$L_1$	Hole pattern	$\phi T_k$	$z \times \phi d$
DN 315	IEC 071	IEC 080	315	395	3	375	DIN 24154-3	355	8 X 10
DN 355	IEC 071	IEC 080	355	435	3	375	DIN 24154-3	395	8 X 10
DN 400	IEC 071	IEC 080	400	480	3	450	DIN 24154-3	450	8 X 12
DN 450	IEC 071	IEC 090	450	530	3	450	DIN 24154-3	500	8 X 12
DN 500	IEC 071	IEC 090	500	590	3	540	DIN 24154-3	560	12 X 12
DN 560	IEC 080 IEC 132	IEC 112 IEC 160	560 560	660 660	3 3	500 750	DIN 24154-3 DIN 24154-3	620 620	12 X 12 12 X 12
DN 630	IEC 090 IEC 132	IEC 112 IEC 160	630 630	730 730	3 3	500 750	DIN 24154-3 DIN 24154-3	690 690	12 X 12 12 X 12
DN 710	IEC 090 IEC 132	IEC 112 IEC 160	710 710	810 810	3 3	500 700	DIN 24154-3 DIN 24154-3	770 770	16 X 12 16 X 12
DN 800	IEC 090 IEC 132	IEC 112 IEC 160	800 800	900 900	3 3	500 700	DIN 24154-3 DIN 24154-3	860 860	16 X 12 16 X 12
DN 900	IEC 100 IEC 160	IEC 132 IEC 180	900 900	1005 1005	4 4	640 850	DIN 24154-3 DIN 24154-5	970 970	16 X 15 16 X 15
DN 1000	IEC 112 IEC 160	IEC 132 IEC 200	1000 1000	1105 1105	4 4	640 850	DIN 24154-3 DIN 24154-4	1070 1070	16 X 15 16 X 15
DN 1120	IEC 132 IEC 225	IEC 200 IEC 225	1120 1120	1260 1260	4 4	850 1000	DIN 24154-3 DIN 24154-6	1190 1190	20 X 15 20 X 15
DN 1250	IEC 132 IEC 225	IEC 200 IEC 250 IEC 280	1250 1250 1250	1390 1390 1390	5 5 5	850 1000 1170	DIN 24154-3 DIN 24154-4 DIN 24154-4	1320 1320 1320	20 X 15 20 X 15 20 X 15
DN 1400	IEC 160 IEC 250	IEC 225 IEC 315	1400 1400	1540 1540	5 6	950 1360	DIN 24154-3 DIN 24154-6	1470 1470	20 X 15 20 X 15
DN 1600	IEC 160 IEC 250	IEC 225 IEC 315	1600 1600	1760 1760	5 6	950 1360	DIN 24154-3 DIN 24154-4	1680 1680	24 X 19 24 X 19

# Fan Specification

## AXC(A) Direct Driven Axial Fans

### Type: AXC(A)

#### Unit consisting of:

- The fan casing from hot-dip galvanized steel in accordance with EN ISO 1641. Flanges press formed on inlet and outlet side of casing . Flanges and hole pattern in accordance with DIN 24154-3. Inspection hole to verify correct direction of rotation of the fan impeller.
- Adjustable impeller manufactured from die cast aluminium . Balanced statically and dynamically in accordance with DIN ISO 1940-1, to quality Q = 6,3.
- Single or three phase IEC motor. Insulation class F; protection class IP 55; design B3; with cold conductor for motor protection; motor in the air stream. Motor pre-wired to the terminal box positioned at the outer casing. Single or two speed motors available. Speed controllable by frequency converter .

### Technical data

#### Fan

Air volume (1,2 kg/m³)	[m³/h]	_____
Static pressure drop	[Pa]	_____
Dynamic pressure drop	[Pa]	_____
Absorbed impeller		_____
Power at shaft P²	[kW]	_____
Total efficiency	[%]	_____
Sound Power Level LW	[dB(A)]	_____

#### Motor

Rated power at shaft P²	[kW]	_____
Rated current	[A]	_____
Rated speed	[rpm]	_____
Voltage / Frequency	[V/Hz]	_____

#### Brand:

Systemair

#### Type:

AXC(A)\_\_\_\_-\_\_/\_-\_\_-\_\_-\_\_

Dimensions: (connection dia./ length)	[mm ]	_____
Weight: (with out accessories)	[kg]	_____

#### Accessories:

Sound attenuator	RSA	_____
Non return damper (self acting)	LRK	_____
Set (2 pieces) mounting feet, horizontal assembly	MFA	_____
Set (4 pieces) mounting bracket, vertical assembly	MP	_____
Set (4 pieces) AV rubber mounts	SD	_____
Set (4 pieces) AV sprung mounts	FSD	_____
Flexible connection	EV-AXC	_____
Counterflange	GFL	_____
Inlet cone	ESD -F	_____
Protection guard for inlet cone	SG	_____
Protection guard	SG	_____
On- / Off- switch	REV	_____

## Notes:

Good climate is the basis for health, performance and well-being.

It is the provision of efficient ventilation and air conditioning systems that drives us forward, as well as the simplification of the work of the planner and installer. Based on the basic values of simplicity and reliability, we develop, produce and distribute high-quality ventilation and air conditioning systems.





[www.systemair.com](http://www.systemair.com)