

LOCATE SALES REP

FIND SERVICE REP



CENTRIFUGAL UPBLAST DIRECT DRIVE FAN

(DU-HRA)

Direct Drive. For drawing more air under moderate static pressures, well suited for commercial kitchen applications.

Air Volume: 2 – 22,500 cfm

Maximum SP: 4" wg. @ standard air density

CONTACT SALES REP >

Features

Options

Certifications

Resources

Models

- > **DU10HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 9" wheel.
- > **DU12HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 10-1/2" wheel.
- > **DU25HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 11-3/4" wheel.
- > **DU30HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 11-3/4" Wheel.
- > **DU33HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 11-3/4" wheel.
- > **DU50HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 13-3/4" wheel.
- > **DU75HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 15-3/4" wheel.
- > **DU85HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 15-3/4" wheel.
- > **DU180HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with, disconnect switch and 18-3/4" wheel.
- > **DU200HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with disconnect switch and 20-3/4" wheel.
- > **DU240HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with disconnect switch and 24" wheel.
- > **DU300HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with disconnect switch and 30" wheel.
- > **DU360HRA** High Speed Direct Drive Centrifugal Upblast Exhaust Fan with disconnect switch and 36" wheel.

LOG IN FOR PARTS >

LOCATE SALES REP

FIND SERVICE REP

RESOURCE LIBRARY

SPECBUILDER

CONTACT US



CENTRIFUGAL UPBLAST DIRECT DRIVE FAN

(DU-HRA)

Direct Drive. For drawing more air under moderate static pressures, well suited for commercial kitchen applications.

Air Volume: 2 – 22,500 cfm

Maximum SP: 4" wg. @ standard air density

[CONTACT SALES REP >](#)

Features

Options

Certifications

Resources

Models

RuppAir certifies that Model DU10HRA thru DU360HRA shown herein are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and Publication 311, and comply with the requirements of the AMCA Certified Rating Program.

Models DU10HRA thru DU360HRA are ETL Listed under file number 102628244PRT-001 and comply with UL705 (electrical) Standards and CSA Std C22.2, No 113.

Models DU12HRA thru DU360HRA are ETL Listed under file number 103336443COL-001 and comply with UL762 Standards.

Catalog #110R

June 2019

