


AIRLINE LOUVERS

LSA4538

- 4.00" CHANNEL FRAME
- 37.5° ANGLE STORM BLADE
- EXTRUDED ALUMINUM 6063-T5 ALLOY
- MATERIAL THICKNESS - NOMINAL
.081" FRAME .081" BLADE
- 20 psf WINDLOAD

- STAINLESS STEEL HARDWARE
- FINISH:
 - MILL ALUMINUM
 - CLEAR ANODIZED
 - BAKED ENAMEL
 - COLOR ANODIZED
 - KYNAR 500
- SCREENS (OPTIONAL)
REF: SCREEN SUBMITTAL

- MULLION (AS REQUIRED):
 - HIDDEN
 - EXPOSED
- ONE PIECE CONSTRUCTION SIZE
MINIMUM: 12" x 12"
MAXIMUM: 120" x 90"
(SINGLE SECTION)




SECTION VIEW
NOT TO SCALE




Airline LOUVERS certifies that the model LSA4538 Louver shown heron is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA Certified Ratings Seal applies to air performance ratings and water penetration ratings.

BLADE BRACE
HIDDEN VERTICAL
BLADE SUPPORT



TOP VIEW
NOT TO SCALE



FRONT VIEW
NOT TO SCALE

LSA4538

ITEM	QTY	MODEL		WALL OPENING		OPTIONAL ACCESSORIES				OPERATOR TYPE	IDENTIFICATION/LOCATION
		STYLE	FLANGE	'A' WIDTH	'B' HEIGHT	EXTERIOR MOUNTED SCREEN	EXTENDED SILL	U-FRAMED SCREENS	HIDDEN MULLION VERT		

AIRLINE
LOUVERS
A NYSTROM BUILDING PRODUCTS COMPANY

Toll-Free: 800-547-2635

Fax: 800-317-8770

Internet: www.airlinelouvers.com

e-mail: info@airlinelouvers.com

PROJECT:

CONTRACTOR:

ARCHITECT:

DRAWN BY:
CMR

REV. DATE:
01-03

QUANTITY:

DATE:

TITLE:
LSA4538

AIRLINE LOUVERS

LSA4S38

PERFORMANCE DATA


AMCA Standard 500 provides a reasonable basis for testing and rating louvers. Testing to AMCA 500 is performed under a certain set of laboratory conditions. This does not guarantee that other conditions will not occur in the actual environment where louvers must operate.

The louver system should be designed with a reasonable safety factor for louver performance. To ensure protection from water carryover, design with a performance level somewhat below maximum desired pressure drop and .01 oz./sq. ft. of water penetration.

WATER PENETRATION

Test size 48" wide x 48" high (1219 x 1219)

Beginning point of water penetration at .01 oz./sq. ft. is 696 fpm (212 m/min).



FREE AREA GUIDE


Free Area Guide shows free area in ft² and m² for various sizes

Width – Inches and Meters

Height – Inches and Meters	12		18		24		30		36		42		48		54		60		66		72		78		84		90		96		102		108		114		120		
		0.30	0.46	0.61	0.76	0.91	1.07	1.22	1.37	1.52	1.68	1.83	1.98	2.13	2.29	2.44	2.59	2.74	2.89	3.04	3.19	3.34	3.49	3.64	3.79	3.94	4.09	4.24	4.39	4.54	4.69	4.84	4.99	5.14	5.29	5.44	5.59		
12	0.34	0.54	0.74	0.95	1.15	1.35	1.56	1.76	1.96	2.16	2.37	2.57	2.77	2.98	3.18	3.38	3.58	3.79	3.99	0.30	0.03	0.05	0.07	0.09	0.11	0.13	0.14	0.16	0.18	0.20	0.22	0.24	0.26	0.28	0.30	0.31	0.33	0.35	0.37
18	0.61	0.97	1.34	1.70	2.06	2.43	2.79	3.16	3.52	3.89	4.25	4.62	4.98	5.34	5.71	6.07	6.44	6.80	7.17	0.46	0.06	0.09	0.12	0.16	0.19	0.23	0.26	0.29	0.33	0.36	0.40	0.43	0.46	0.50	0.53	0.56	0.60	0.63	0.67
24	0.79	1.27	1.75	2.22	2.70	3.18	3.65	4.13	4.61	5.08	5.56	6.04	6.51	6.99	7.47	7.94	8.42	8.90	9.37	0.61	0.07	0.12	0.16	0.21	0.25	0.30	0.34	0.38	0.43	0.47	0.52	0.56	0.61	0.65	0.69	0.74	0.78	0.83	0.87
30	1.06	1.70	2.34	2.98	3.62	4.25	4.89	5.53	6.17	6.81	7.44	8.08	8.72	9.36	10.00	10.63	11.27	11.91	12.55	0.76	0.10	0.16	0.22	0.28	0.34	0.40	0.45	0.51	0.57	0.63	0.69	0.75	0.81	0.87	0.93	0.99	1.05	1.11	1.17
36	1.33	2.13	2.93	3.73	4.53	5.33	6.13	6.93	7.73	8.53	9.33	10.13	10.93	11.73	12.53	13.33	14.12	14.92	15.72	0.91	0.12	0.20	0.27	0.35	0.42	0.50	0.57	0.64	0.72	0.79	0.87	0.94	1.02	1.09	1.16	1.24	1.31	1.39	1.46
42	1.60	2.56	3.52	4.48	5.45	6.41	7.37	8.33	9.29	10.25	11.21	12.17	13.13	14.09	15.06	16.02	16.98	17.94	18.90	1.07	0.15	0.24	0.33	0.42	0.51	0.60	0.69	0.77	0.86	0.95	1.04	1.13	1.22	1.31	1.40	1.49	1.58	1.67	1.76
48	1.79	2.86	3.93	5.01	6.08	7.15	8.23	9.30	10.37	11.45	12.52	13.59	14.67	15.74	16.81	17.89	18.96	20.03	21.11	1.22	0.17	0.27	0.37	0.47	0.57	0.67	0.77	0.86	0.96	1.06	1.16	1.26	1.36	1.46	1.56	1.66	1.76	1.86	1.96
54	2.06	3.29	4.53	5.76	7.00	8.23	9.47	10.70	11.94	13.17	14.40	15.64	16.87	18.11	19.34	20.58	21.81	23.05	24.28	1.37	0.19	0.31	0.42	0.54	0.65	0.77	0.88	1.00	1.11	1.22	1.34	1.45	1.57	1.68	1.80	1.91	2.03	2.14	2.26
60	2.33	3.72	5.12	6.52	7.91	9.31	10.70	12.10	13.50	14.89	16.29	17.68	19.08	20.48	21.87	23.27	24.67	26.06	27.46	1.52	0.22	0.35	0.48	0.61	0.74	0.87	1.00	1.13	1.26	1.38	1.51	1.64	1.77	1.90	2.03	2.16	2.29	2.42	2.55
66	2.60	4.15	5.71	7.27	8.83	10.38	11.94	13.50	15.06	16.61	18.17	19.73	21.29	22.85	24.40	25.96	27.52	29.08	30.63	1.68	0.24	0.39	0.53	0.68	0.82	0.97	1.11	1.26	1.40	1.55	1.69	1.83	1.98	2.12	2.27	2.41	2.56	2.70	2.85
72	2.78	4.45	6.12	7.79	9.46	11.13	12.80	14.47	16.14	17.81	19.48	21.15	22.82	24.49	26.16	27.83	29.50	31.17	32.84	1.83	0.26	0.41	0.57	0.72	0.88	1.04	1.19	1.35	1.50	1.66	1.81	1.97	2.12	2.28	2.43	2.59	2.74	2.90	3.05
78	3.05	4.88	6.71	8.55	10.38	12.21	14.04	15.87	17.70	19.53	21.37	23.20	25.03	26.86	28.69	30.52	32.35	34.18	36.02	1.98	0.28	0.45	0.62	0.79	0.97	1.14	1.31	1.48	1.65	1.82	1.99	2.16	2.33	2.50	2.67	2.84	3.01	3.18	3.35
84	3.32	5.31	7.31	9.30	11.29	13.29	15.28	17.27	19.26	21.26	23.25	25.24	27.23	29.23	31.22	33.21	35.21	37.20	39.19	2.13	0.31	0.49	0.68	0.86	1.05	1.24	1.42	1.61	1.79	1.98	2.16	2.35	2.53	2.72	2.90	3.09	3.27	3.46	3.64
90	3.59	5.74	7.90	10.05	12.21	14.36	16.52	18.67	20.82	22.98	25.13	27.29	29.44	31.60	33.75	35.90	38.06	40.21	42.37	2.29	0.33	0.53	0.73	0.93	1.14	1.34	1.54	1.74	1.94	2.14	2.34	2.54	2.74	2.94	3.14	3.34	3.54	3.74	3.94

54% free area based on 48" X48" unit

PRESSURE DROP



Ratings do not include the effects of a bird screen