

For Mounting Heights To 10' (environmental separation) and 8' (insect control)

STANDARD CONSTRUCTION

- 14" high x 15" deep
- 1/2 hp three speed motor(s)
- Factory installed fan speed switch
- White or black aluminum exterior cover (Optional: Custom Color or Stainless)
- Wall & Top Mounting
- Optional: Filter (washable)



Berner International Corporation certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (unheated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

5 Year Limited Warranty



MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Net Wt. (lbs)
CHC10-1036A	36.00	3,284	2,062	1,804	73%	0.78	1 @ 1/2	50
CHC10-1042A	42.00	3,592	1,748	1,784	54%	0.74	1 @ 1/2	52
CHC10-1048A	48.00	3,614	1,515	1,768	62%	0.75	1 @ 1/2	53
CHC10-1060A	60.00	3,319	1,184	1,726	48%	0.73	1 @ 1/2	54
CHC10-2060A	60.00	3,711	1,801	2,626	74%	1.21	2 @ 1/2	70
CHC10-2072A	72.00	3,284	2,062	3,608	73%	1.56	2 @ 1/2	84
CHC10-2084A	87.00	3,592	1,687	3,568	54%	1.49	2 @ 1/2	104
CHC10-2096A	99.00	3,614	1,470	3,536	62%	1.49	2 @ 1/2	106
CHC10-3096A	99.00	3,284	1,841	4,430	73%	1.99	3 @ 1/2	120
CHC10-2108A	111.00	3,319	1,295	3,494	48%	1.48	2 @ 1/2	107
CHC10-3108A	111.00	3,284	2,006	5,412	73%	2.34	3 @ 1/2	150
CHC10-2120A	116.25	3,319	1,222	3,452	48%	1.47	2 @ 1/2	108
CHC10-3120A	116.25	3,284	1,908	5,392	54%	2.30	3 @ 1/2	152

NOTE: Operation at 50 Hz will generate approximately a 17% reduction in air performance.

See sheet EP-114 for amp draws/total load requirements.

MODEL NUMBER CONFIGURATION

CHC10-1 036 A A-R-SS

Series	# of Motors	Opening Width	Heat	Voltage	Opt. Switch	Cabinet Finish
CHC10	1, 2, 3	036" - 120"	A=Ambient	*A=120/1/60 B=208/1/60 J=240/1/60 Z=480/3/60 Q=600/3/60 V=220/1/50	Remote Switch	White (leave blank) BK=Black Opt. Cabinet Finish SS=Stainless Steel CC=Custom Color

*Suitable for 50hz

for Standard offering, leave options (Opt.) blank
make sure to specify Cabinet Finish if other than white

VELOCITY PROJECTION: Model CHC10-1036A					
Distance from Nozzle (in)	40	80	120	160	200
Core Velocity (fpm)	1270	1100	1000	940	910
Uniformity (%)	92	91	91	88	86

Sound level measured 10' (3m) from the unit in free field:

1 motor:	Low/Medium/High Speed:	64/65/66 dBA
2 motors 60":	Low/Medium/High Speed:	66/67/68 dBA
2 motors:	Low/Medium/High Speed:	67/68/69 dBA
3 motors:	Low/Medium/High Speed:	67/68/69 dBA

Berner reserves the right to alter specifications without prior notice.