

## Application

The EXD-437 combination louver features stationary drainable louver blades to protect against water penetration and an integral control damper to allow positive shutoff protection of air intake and exhaust openings. The EXD-437 is available in a wide array of anodized and painted finishes including custom color matching. These units are also available with a variety of factory mounted electric or pneumatic actuators.

## Standard Construction

- Material:** Mill finish 6063-T5 extruded aluminum.
- Frame:** 4" deep × 0.081" thick (102 × 2) channel.
- Blades:** 37½° × 0.081" (2) thick combination style.
- Screen:** ½" × 0.063" (12.7 × 1.6) expanded and flattened aluminum.
- Low leakage seals:** TPV blade edge and flexible metal jamb.
- Axles:** ½" (13) diameter plated steel hex.
- Linkage:** Concealed in frame.
- Bearings:** Synthetic.
- Mullion:** Visible.
- Minimum Size:** 12" × 12" (305 × 305)
- Maximum Size:** Single section:  
48" × 96" (1219 × 2436) with low leakage seals.  
60" × 96" (1524 × 2436) without low leakage seals.  
Multiple section: Unlimited

## Options

- Factory finish:
  - High Performance Fluoropolymer - 100% resin Newlar®/ 70% resin Kynar®
  - Baked Enamel/Polyester
  - Clear or Color Anodized, Class 1
  - Prime Coat
- 1½" (38) flange frame.
- Welded construction.
- Alternate bird or insect screens.
- Insulated or non-insulated blank-off panels.
- Filter racks.
- Hinged frame.
- Head and/or sill flashing.
- Factory mounted electric or pneumatic actuator.
- Installation hardware:
  - Clip angles
  - Continuous angles
- No low leakage seals.

## Ratings


**Free Area:** [48" × 48" (1219 × 1219) unit]: 6.9 ft<sup>2</sup> (0.64 m<sup>2</sup>)  
43.0%

### Performance @ Beginning Point of Water Penetration

**Free Area Velocity:** 1172 fpm (5.95 m/s)  
**Air Volume Delivered:** 8,134 cfm (3.84 m<sup>3</sup>/s)  
**Pressure Loss:** 0.17 in.wg. (42 Pa)

**Velocity@ 0.15 in.wg. Pressure Loss:** 1085 fpm (5.51 m/s)

**Design Load:** 30 psf




Model **EXD-437**  
(standard)


\*Louver dimensions furnished approximately ½" (13) undersize.

**Vertical Section**


†Screen adds approximately 3/16" (5) to louver depth.



**Vertical Mullion**  
(standard)



**Horizontal Mullion**  
(standard)



**Flange Frame**  
(optional)



### Certified Ratings:

Pottorff certifies that the model EXD-437 shown herein is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA Certified Ratings seal applies to water penetration and air performance ratings.

# Performance Data

## Free Area (ft<sup>2</sup>)


		Width (Inches)								
		12	18	24	30	36	42	48	54	60
Height (Inches)	12	0.24	0.38	0.53	0.67	0.81	0.95	1.10	1.24	1.38
	18	0.52	<b>0.83</b>	1.15	1.46	1.77	2.08	2.40	2.71	3.02
	24	0.66	1.06	<b>1.46</b>	1.85	2.25	2.65	3.04	3.44	3.84
	30	0.94	1.51	2.08	<b>2.64</b>	3.21	3.78	4.34	4.91	5.48
	36	1.09	1.74	2.39	3.04	<b>3.69</b>	4.34	4.99	5.64	6.29
	42	1.37	2.19	3.01	3.83	4.65	<b>5.47</b>	6.29	7.11	7.93
	48	1.51	2.41	3.32	4.22	5.13	6.03	<b>6.94</b>	7.84	8.75
	54	1.79	2.86	3.94	5.01	6.09	7.16	8.24	<b>9.31</b>	10.38
	60	1.93	3.09	4.25	5.41	6.57	7.73	8.88	10.04	<b>11.20</b>
	66	2.21	3.54	4.87	6.20	7.53	8.85	10.18	11.51	12.84
	72	2.35	3.77	5.18	6.59	8.01	9.42	10.83	12.24	13.66
	78	2.64	4.22	5.80	7.38	8.96	10.55	12.13	13.71	15.29
	84	2.78	4.44	6.11	7.78	9.44	11.11	12.78	14.44	16.11
90	3.06	4.90	6.73	8.57	10.40	12.24	14.08	15.91	17.75	
96	3.20	5.12	7.04	8.96	10.88	12.80	14.72	16.64	18.57	



**Certified Ratings:**  
Pottorff certifies that the model EXD-437 shown herein is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA Certified Ratings seal applies to water penetration and air performance ratings.

## Pressure Loss

(Data corrected to standard air density)



Louver Test Size = 48" x 48" (1219 x 1219)

Pressure loss tested in accordance with Figure 5.5 of AMCA Standard 500-L

## Selection Criteria

Follow the steps listed below to calculate the louver size needed to satisfy the required air volume while minimizing the adverse effects of water penetration and pressure loss.


1. Determine the Free Area Velocity (FAV) at the maximum allowable pressure loss using the *Pressure Loss* chart to the left. While job conditions vary, typically, the maximum allowable pressure loss should not exceed 0.15 in.wg., and the FAV for 0.15 in.wg. pressure loss is listed on the front page of this sheet.
2. **Intake Applications** If the FAV at the Beginning Point of Water Penetration (shown below) is less than the FAV from step 1, then use the FAV at the Beginning Point of Water Penetration in step 3, otherwise use the FAV from step 1.
- Exhaust Applications** Use the FAV from step 1 in step 3.
3. Calculate the total louver square footage required using the following equation.

$$\frac{\text{Required Air Volume}}{\text{cfm}} \div \frac{\text{FAV}}{\text{fpm}} = \frac{\text{Required Louver (Free-Area) Size}}{\text{ft}^2}$$

4. Using the *Free Area* chart above, select a louver width and height that yields a free area ft<sup>2</sup> greater than or equal to the required louver size calculated in step 3.

## Water Penetration

Beginning Point of Water Penetration = 1172 fpm



## Water Penetration

AMCA defines the beginning point of water penetration as the free area velocity at the intersection of a simple linear regression of test data and the line of 0.01 ounces of water per square foot of free area and is measured through a 48" x 48" louver during a 15 minute period. The AMCA water penetration test provides a method for comparing louver models and designs as to their efficiency in resisting the penetration of rainfall under specific lab conditions. Pottorff recommends that intake louvers are selected with a reasonable margin of safety below the beginning point of water penetration in order to avoid unwanted penetration during severe storm conditions.

Information is subject to change without notice or obligation.

**NOTE:** Dimensions in parentheses ( ) are millimeters.