

For Mounting Heights To 8' (environmental separation)

STANDARD CONSTRUCTION

- 11" high x 24" deep
- 1/2 hp motor(s) - ten speeds
- Factory installed Intelliswitch digital controller
- White powder coated exterior (Optional: Custom Color or Stainless)
- Wall & Top Mounting
- High efficiency, low noise Pro-V Nozzle
- Optional: Decorative adaptor
- Optional: Wi-Fi Controller, works with the Berner App



Berner International certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (unheated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

5 Year Limited Warranty



MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Net Wt. (lbs)
AED08-1036A	36.50	3,255	1,680	1,155	79%	0.34	1 @ 1/2	111
AED08-1042A	42.50	2,481	1,812	1,305	71%	0.44	1 @ 1/2	135
AED08-1048A	48.50	2,958	1,838	1,685	78%	0.49	1 @ 1/2	158
AED08-1060A	59.50	3,168	1,697	1,912	71%	0.56	1 @ 1/2	185
AED08-2072A	73.00	3,255	1,680	2,310	79%	0.68	2 @ 1/2	225

NOTE: Operation at 50 Hz will generate approximately a 17% reduction in air performance.

See sheet EP-230 for amp draws/total load requirements.

MODEL NUMBER CONFIGURATION

AED08-1 036 A A -R-WCA-CC

Series	# of Motors	Opening Width	Heat	Voltage	Opt. Display	Opt. Control	Opt. Cabinet Finish
AED08	1, 2	036" - 72"	A=Ambient	*A=120/1/60 B=208/1/60 J=240/1/60 V=220/1/50	R=Remote Display Intelliswitch	WCA=Wi-Fi Controller Berner App	SS=Stainless Steel CC=Custom Color

*Suitable for 50hz for Standard offering, leave options (Opt.) blank

VELOCITY PROJECTION: Model AED08-1036A			
Distance from Nozzle (in)	24	36	48
Core Velocity (fpm)	1483	1181	961
Uniformity (%)	65	74	77

Sound level measured 10' (3m) from the unit in free field:
 AED08-1036 & AED08-1042: Min./Max. Speed: 58/62 dBA
 AED08-1048 & AED08-1060: Min./Max. Speed: 60/64 dBA
 AED08-2072: Min./Max. Speed: 61/65 dBA

Sound data is not AMCA certified.

Berner reserves the right to alter specifications without prior notice.